

# VIP-3/SC/RJ45 - Interface module



2900701

<https://www.phoenixcontact.com/in/products/2900701>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

VARIOFACE module with screw connection and RJ45 connector



## Your advantages

- RJ45 connector, CAT3, 8-pos.
- Screw connection
- 1:1 connection
- Metal foot

## Commercial Data

Item number	2900701
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	CK2
Product Key	CK2471
Catalog Page	Page 559 (C-5-2019)
GTIN	4046356547802
Weight per Piece (including packing)	84.4 g
Weight per Piece (excluding packing)	84.4 g
Customs tariff number	85366990
Country of origin	US

# VIP-3/SC/RJ45 - Interface module



2900701

<https://www.phoenixcontact.com/in/products/2900701>

## Technical Data

### Product properties

Product type	Interface module
Product family	VARIOFACE Professional
Number of positions	8

### Electrical properties

Nominal voltage $U_N$	48 V AC/DC
Max. current carrying capacity per branch	1 A
Max. total current of all branches	4 A

### Connection data

#### Field level

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M 3
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

#### Controller level

Connection method	RJ45 jack
Number of connections	1
Number of positions	8

### Signaling

Status display	No
Status display present	No

### Dimensions

Width	26.9 mm
Height	69 mm
Depth	62 mm

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

### Standards and regulations

Standards/regulations	EN 50178
-----------------------	----------

# VIP-3/SC/RJ45 - Interface module



2900701

<https://www.phoenixcontact.com/in/products/2900701>

## Mounting

Mounting type	DIN rail mounting
Mounting position	any

# VIP-3/SC/RJ45 - Interface module




2900701

<https://www.phoenixcontact.com/in/products/2900701>

## Drawings

Circuit diagram




# VIP-3/SC/RJ45 - Interface module




2900701


<https://www.phoenixcontact.com/in/products/2900701>


## Approvals

 <b>CSA</b> Approval ID: 2122203				
	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	48 V	1 A	28 - 12	-

 <b>cUL Recognized</b> Approval ID: FILE E 238705				
	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	48 V	1 A	30 - 12	-

 <b>UL Recognized</b> Approval ID: FILE E 238705				
	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	48 V	1 A	30 - 12	-

 <b>EAC</b> Approval ID: RU C-DE.A*30.B.01742				
---	--	--	--	--

 <b>CSAus</b> Approval ID: 2122203				
	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	48 V	1 A	28 - 12	-

# VIP-3/SC/RJ45 - Interface module



2900701

<https://www.phoenixcontact.com/in/products/2900701>

## Classifications

### ECLASS

ECLASS-11.0	27141152
ECLASS-13.0	27141152
ECLASS-12.0	27141152

### ETIM

ETIM 8.0	EC002780
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# VIP-3/SC/RJ45 - Interface module



2900701

<https://www.phoenixcontact.com/in/products/2900701>

## Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.  
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420  
[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)