

# Product data sheet

Specifications



Miniature circuit breaker (MCB),  
Acti9 C120H, 3P, 100A, D curve,  
15000A (IEC/EN 60898-1), 15kA  
(IEC/EN 60947-2)

A9N18513

## Main

|                           |                                                                                                                                                                                                                                                                                                                                       |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product          | C120                                                                                                                                                                                                                                                                                                                                  |
| Range                     | Acti9                                                                                                                                                                                                                                                                                                                                 |
| Product name              | C120                                                                                                                                                                                                                                                                                                                                  |
| Product or component type | Miniature circuit-breaker                                                                                                                                                                                                                                                                                                             |
| Device short name         | C120H                                                                                                                                                                                                                                                                                                                                 |
| Device application        | Distribution                                                                                                                                                                                                                                                                                                                          |
| Poles description         | 3P                                                                                                                                                                                                                                                                                                                                    |
| Number of protected poles | 3                                                                                                                                                                                                                                                                                                                                     |
| [In] rated current        | 100 A at 30 °C                                                                                                                                                                                                                                                                                                                        |
| Network type              | AC                                                                                                                                                                                                                                                                                                                                    |
| Trip unit technology      | Thermal-magnetic                                                                                                                                                                                                                                                                                                                      |
| Curve code                | D                                                                                                                                                                                                                                                                                                                                     |
| Breaking capacity         | 15000 A Icn at 230...400 V AC 50/60 Hz conforming to EN/IEC 60898-1<br>10 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>15 kA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>30 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>15 kA Icu at <= 375 V DC conforming to EN/IEC 60947-2 |
| Suitability for isolation | Yes conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                         |

## Complementary

|                                        |                                                                                                                                                                                                                                                                                                                                       |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network frequency                      | 50/60 Hz                                                                                                                                                                                                                                                                                                                              |
| [Ue] rated operational voltage         | <= 375 V DC<br>380...415 V AC 50/60 Hz<br>220...240 V AC 50/60 Hz<br>440 V AC 50/60 Hz<br>230...400 V AC 50/60 Hz                                                                                                                                                                                                                     |
| Magnetic tripping limit                | 10...14 x In                                                                                                                                                                                                                                                                                                                          |
| [Ics] rated service breaking capacity  | 7500 A 50 % conforming to EN/IEC 60898-1 - 230...400 V AC 50/60 Hz<br>5 kA 50 % conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz<br>15 kA 50 % conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz<br>7.5 kA 50 % conforming to EN/IEC 60947-2 - 380...415 V AC 50/60 Hz<br>15 kA 100 % conforming to EN/IEC 60947-2 - <= 375 V DC |
| Limitation class                       | 3 conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                        |
| [Ui] rated insulation voltage          | 500 V AC 50/60 Hz conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                        |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                     |

|                                                  |                                                                                     |
|--------------------------------------------------|-------------------------------------------------------------------------------------|
| Contact position indicator                       | Yes                                                                                 |
| Control type                                     | Toggle                                                                              |
| Local signalling                                 | ON/OFF indication                                                                   |
| Mounting mode                                    | Clip-on                                                                             |
| Mounting support                                 | 35 mm symmetrical DIN rail                                                          |
| Comb busbar and distribution block compatibility | NO                                                                                  |
| 9 mm pitches                                     | 9                                                                                   |
| Height                                           | 81 mm                                                                               |
| Width                                            | 81 mm                                                                               |
| Depth                                            | 73 mm                                                                               |
| Net weight                                       | 0.615 kg                                                                            |
| Colour                                           | White                                                                               |
| Mechanical durability                            | 20000 cycles                                                                        |
| Electrical durability                            | 5000 cycles conforming to IEC 60947-2                                               |
| Locking options description                      | Handle sealable with cable diameter 0.7mm in OFF or ON position                     |
| Connections - terminals                          | Tunnel type terminals1...50 mm² rigid<br>Tunnel type terminals1.5...35 mm² flexible |
| Wire stripping length                            | 15 mm                                                                               |
| Tightening torque                                | 3.5 N.m                                                                             |
| Earth-leakage protection                         | Separate block                                                                      |

## Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Standards                             | EN/IEC 60898-1<br>EN/IEC 60947-2 |
| Product certifications                | EAC                              |
| IP degree of protection               | IP20 conforming to IEC 60529     |
| Pollution degree                      | 3 conforming to IEC 60947-2      |
| Overvoltage category                  | IV                               |
| Tropicalisation                       | 2 conforming to IEC 60068-1      |
| Relative humidity                     | 95 % at 55 °C                    |
| Operating altitude                    | 2000 m                           |
| Ambient air temperature for operation | -30...60 °C                      |
| Ambient air temperature for storage   | -40...70 °C                      |

## Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 6.8 cm |
| Package 1 Width              | 8.1 cm |
| Package 1 Length             | 8.6 cm |
| Package 1 Weight             | 578 g  |
| Unit Type of Package 2       | BB1    |
| Number of Units in Package 2 | 4      |

|                              |          |
|------------------------------|----------|
| Package 2 Height             | 8.6 cm   |
| Package 2 Width              | 9.6 cm   |
| Package 2 Length             | 33.1 cm  |
| Package 2 Weight             | 2.384 kg |
| Unit Type of Package 3       | S03      |
| Number of Units in Package 3 | 24       |
| Package 3 Height             | 30 cm    |
| Package 3 Width              | 30 cm    |
| Package 3 Length             | 40 cm    |
| Package 3 Weight             | 14.75 kg |

Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                 |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)