


MG-CPM-MD

TERMINAL MARKER TAGS, METAL DETECTABLE



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40°C
Maximum operating temperature	130°C
Colour	blue
Number of lines	4

CLASSIFICATION AND DATA ORDERING

Customs code	39269097
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate/ABS
----------	-------------------

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	HB
Cembre internal test	Yes
CEI EN 60950-1	Yes
CEI EN 61010-1 ed.2	Yes
DIN 30643	Yes



MG-CPM-MD

tipo	Sheet elements	Tag format	Silicone-free	S [mm]	Width [mm]	L [mm]	Horizontal pitch between the sheet elements [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant
41068-MD	56	M (modular strip)		1.4	5	10	5.1	1960	1960	
41064-MD	56	S (single)		1.1	5	7	5.1	1960	1960	
41065-MD	48	M (modular strip)		1.1	6	10	6	1680	1680	
41062-MD	80	S (single)		1.3	3	10	3.5	2000	2000	Yes
41160N-MD	48	S (single)		1.4	5	10	5.1	1680	1680	
41261-MD	56	S (single)		1.4	5	10	5	1960	1960	
41263-MD	56	M (modular strip)		1.4	5	10	5	1960	1960	
41365-MD	48	M (modular strip)		1.4	5	10	5.2	1680	1680	
41361-MD	48	M (modular strip)		1.1	6	10	6	1344	1344	
41366-MD	32	M (modular strip)		1.4	8	10	8	1120	1120	
41362-MD	80	S (single)		1.3	3	10	5	2000	2000	Yes
41460-MD	56	S (single)		1.4	5	10	5	1960	1960	
41561-MD	44	S (single)		1.4	5	10	6	1540	1540	Yes
41661-MD	48	S (single)		1.4	5	10	5.2	1680	1680	
41860-MD	56	MF (modular flexible pitch strip)		1.1	5	10	5.5	1960	1960	Yes
46360-MD	56	MF (modular flexible pitch strip)		1.1	4.2	9	5	1960	1960	
46162-MD	48	S (single)		1.4	5	12	5.5	1680	1680	
41760-MD	56	M (modular strip)		1.4	5	12	5.2	1960	1960	
41761-MD	48	M (modular strip)		1.4	6	12	6	1680	1680	
46362-MD	48	S (single)	Yes	1.4	6	12	6.1	1344	1344	Yes
42608-MD	48	M (modular strip)		1.1	5	5	5.1	1680	1680	

