

S-P

ROUND PIN TERMINAL, NON-INSULATED, WITH BRAZED NECK, FOR COPPER CONDUCTORS



Features

TECHNICAL INFORMATION

Minimum operating temperature	-50°C
Maximum operating temperature	150°C
Surface treatment	tin plating
Crimping geometry	indent

WEIGHT AND DIMENSIONS

Tip type	pin
----------	-----

CLASSIFICATION AND DATA ORDERING

Customs code	85369010
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS


Conductor body material	Rame elettrolitico con purezza superiore al 99,95%
Annealing	Yes
Brazed seam	Yes

LOGISTIC

Unit in minimal packaging	100PCE
---------------------------	--------

CERTIFICATIONS

ROHS compliant	Yes
----------------	-----



S1.5-P Range of cable cross section [mm²]
0.25

tipo	B [mm]	P [mm]	L [mm]	A [mm]	Ø [mm]	Cable stripping length [mm]	Ø1 [mm]	Unit in standard packaging [pce]
S1.5-P8	1.6	7.8	12	4.2	1.8	5	3.4	8000
S1.5-P10	1.6	9.8	14	4.2	1.8	5	3.4	8000
S1.5-P12	1.6	12	16.2	4.2	1.8	5	3.4	8000

S2.5-P Range of cable cross section [mm²]
1.5

tipo	B [mm]	P [mm]	L [mm]	A [mm]	Ø [mm]	Cable stripping length [mm]	Ø1 [mm]	Unit in standard packaging [pce]
S2.5-P8	1.6	7.8	12	4.2	2.4	5	4	7000
S2.5-P10	1.6	9.8	14	4.2	2.4	5	4	7000
S2.5-P12	1.6	11.8	16	4.2	2.4	5	4	7000

S6-P Range of cable cross section [mm²]
4

tipo	B [mm]	P [mm]	L [mm]	A [mm]	Ø [mm]	Cable stripping length [mm]	Ø1 [mm]	Unit in standard packaging [pce]
S6-P10	2.2	10.4	16.8	8	3.6	7	5.6	4000
S6-P12	2.2	12.6	19	8	3.6	7	5.6	4000
S6-P14	2.2	14.6	21	8	3.6	7	5.6	3000