

PM

HOLDERS, PLASTICIZED PVC, FOR RIGID TAGS AND CABLE MARKERS



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40°C
Maximum operating temperature	80°C
Colour	transparent

CLASSIFICATION AND DATA ORDERING

Customs code	39269097
--------------	----------

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	V0
--	----



PM-00

Range of cable cross section [mm²]
0.25

Ø [mm]
1.3

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
50000	Plasticised PVC	4.8	10	8000	8000	Yes	Yes
50010	Plasticised PVC	4.8	12	7000	7000	Yes	Yes
50020	Plasticised PVC	4.8	15	6000	6000	Yes	Yes
50030	Plasticised PVC	4.8	18	5000	5000	Yes	Yes
50032	Plasticised PVC	4.8	18	3000	3000	Yes	Yes
50042	Plasticised PVC	4.8	21	1000	1000	Yes	Yes
50052	Plasticised PVC	4.8	23	1000	1000	Yes	Yes
50062	Plasticised PVC	4.8	27	1000	1000	Yes	Yes
50072	Plasticised PVC	4.8	30	500	500	Yes	Yes
50080	Plasticised PVC	4.8	1000	10	10	Yes	Yes

PM-01

Range of cable cross section [mm²]
0.5

Ø [mm]
2

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
50100	Plasticised PVC	5	10	6000	6000	Yes	Yes
50110	Plasticised PVC	5	12	5000	5000	Yes	Yes
50120	Plasticised PVC	5	15	4000	4000	Yes	Yes
50130	Plasticised PVC	5	18	3000	3000	Yes	Yes
50140	Plasticised PVC	5	21	3000	3000	Yes	Yes
50150	Plasticised PVC	5	23	2000	2000	Yes	Yes
50160	Plasticised PVC	5	27	2000	2000	Yes	Yes
50170	Plasticised PVC	5	30	1000	1000	Yes	Yes
50180	Plasticised PVC	5	1000	10	10	Yes	Yes

PM-02

Range of cable cross section [mm²]
2.5

Ø [mm]
3.5

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
50200	Plasticised PVC	5.1	10	4000	4000	Yes	Yes
50210	Plasticised PVC	5.1	12	3000	3000	Yes	Yes
50220	Plasticised PVC	5.1	15	2500	2500	Yes	Yes
50230	Plasticised PVC	5.1	18	2000	2000	Yes	Yes
50240	Plasticised PVC	5.1	21	2000	2000	Yes	Yes
50250	Plasticised PVC	5.1	23	2000	2000	Yes	Yes

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
50260	Plasticised PVC	5.1	27	1000	1000	Yes	Yes
50270	Plasticised PVC	5.1	30	1000	1000	Yes	Yes
50280	Plasticised PVC	5.1	1000	10	10	Yes	Yes

PM-03

Range of cable cross section [mm²]

4

Ø [mm]

4

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
50300	Plasticised PVC	7.6	10	3000	3000	Yes	Yes
50310	Plasticised PVC	7.6	12	2000	2000	Yes	Yes
50320	Plasticised PVC	7.6	15	2000	2000	Yes	Yes
50330	Plasticised PVC	7.6	18	1000	1000	Yes	Yes
50340	Plasticised PVC	7.6	21	1000	1000	Yes	Yes
50350	Plasticised PVC	7.6	23	1000	1000	Yes	Yes
50360	Plasticised PVC	7.6	27	1000	1000	Yes	Yes
50370	Plasticised PVC	7.6	30	500	500	Yes	Yes
50380	Plasticised PVC	7.6	1000	10	10	Yes	Yes

PM-04

Range of cable cross section [mm²]

10

Ø [mm]

6

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
50400	Plasticised PVC	9	10	2000	2000	Yes	Yes
50410	Plasticised PVC	9	10	1000	1000	Yes	Yes
50420	Plasticised PVC	9	15	1000	1000	Yes	Yes
50430	Plasticised PVC	9	18	1000	1000	Yes	Yes
50440	Plasticised PVC	9	21	500	500	Yes	Yes
50450	Plasticised PVC	9	23	500	500	Yes	Yes
50460	Plasticised PVC	9	27	500	500	Yes	Yes
50470	Plasticised PVC	9	30	500	500	Yes	Yes
50480	Plasticised PVC	9	1000	10	10	Yes	Yes

PM-05

Range of cable cross section [mm²]

25

Ø [mm]

9

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
50500N	Plasticised PVC	15.9	10	1000	1000		Yes
50510N	Plasticised PVC	15.9	12	1000	1000		Yes
50521N	Plasticised PVC	15.9	15	500	500		Yes

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
50530	Plasticised PVC	15.9	18	250	250	Yes	Yes
50540	Plasticised PVC	15.9	21	250	250	Yes	Yes
50550	Plasticised PVC	15.9	23	250	250	Yes	Yes
50560	Plasticised PVC	15.9	27	250	250	Yes	Yes
50570	Plasticised PVC	15.9	30	250	250	Yes	Yes
50580	Plasticised PVC	15.9	1000	10	10	Yes	Yes

PM-06

Range of cable cross section [mm²]

70

Ø [mm]

14

tipo	Material	Silicone-free	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
50600	Plasticised PVC		20.4	10	500	500	Yes	Yes
50610N	Plasticised PVC		20.4	12	500	500		Yes
50620		Yes	4	15	250	250	Yes	
50620N	Plasticised PVC		20.4	15	300	300		Yes
50630	Plasticised PVC		20.4	18	250	250	Yes	Yes
50640	Plasticised PVC		20.4	21	100	100	Yes	Yes
50650	Plasticised PVC		20.4	23	100	100	Yes	Yes
50660	Plasticised PVC		20.4	27	100	100	Yes	Yes
50670	Plasticised PVC		20.4	30	100	100	Yes	Yes
50680	Plasticised PVC		20.4	1000	10	10	Yes	Yes

CEMBRE

Via Serenissima, 9 - 25135
Brescia - ITALY