

NL-P

CONNECTOR SLEEVE, PRE-INSULATED WITH POLYAMIDE PA6.6, FOR COPPER CONDUCTORS



Features

TECHNICAL INFORMATION

Minimum operating temperature	-20°C
Maximum operating temperature	115°C
Threshold of operating temperature for short periods	130°C
Type of insulation	full
Surface treatment	tin plating

MATERIAL COMPOSITION AND TREATMENTS

Conductor body material	Rame elettrolitico con purezza superiore al 99,95%
Annealing	Yes

LOGISTIC


Unit in minimal packaging	100PCE
---------------------------	--------

CLASSIFICATION AND DATA ORDERING

Customs code	85369010
--------------	----------

CERTIFICATIONS

EN 45545-2 certification	HL2
--------------------------	-----



NL-P

tipo	Insulated cover colour	Crimping geometry	Range of cable cross section [mm²]	L [mm]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]	ROHS compliant
NL03-P	white	indent; radial	0.25 - 1.5	21	6	21	7.9		2.6	7	1000	Yes
NL06-P	white	indent; radial	1.5 - 2.5	19.9	6.8	19.9	7.9	9.5	3	8	1000	Yes
NL06-PB	blue	indent; radial	1.5 - 2.5	13.6	6	13.6	6.5	8.3	2.42	7	1500	Yes
NL1-P	white	indent; radial	4 - 6	21.5	7.7	21.5	10.5	12.3	3.6	9	500	Yes
NL1-PG	yellow	indent; radial	4 - 6	17.8	9	17.8	9.2	11	3.6	10	1000	Yes



