

C-CST

SLEEVE CONNECTOR, TIN-PLATED, FOR COPPER CONDUCTORS



CERTIFICATIONS & APPROVALS



USDA

Features

TECHNICAL INFORMATION


Minimum operating temperature	-50°C
Maximum operating temperature	150°C
Surface treatment	tin plating
Crimping geometry	oval

MATERIAL COMPOSITION AND TREATMENTS

Conductor body material	Rame elettrolitico con purezza superiore al 99,95%
Annealing	Yes

CLASSIFICATION AND DATA ORDERING

Customs code	85369010
--------------	----------



C-CST

tipo	Type of branch circuit	Cross section range of the through cable [mm²]	Cross section range of the branch cable [mm²]	C [mm]	L [mm]	B [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant
C6-C6ST	tap connection; joint connection	2.5 - 6	1.5 - 6	9	9.8	6.4	100	1000	Yes
C10-C10ST	tap connection; joint connection	10	1.5 - 10	12	12.6	8.4	100	500	Yes
C16-C16ST	tap connection; joint connection	16	1.5 - 16	17	19.4	12	100	400	Yes
C25-C10ST	tap connection; joint connection	16 - 25	1.5 - 10	17	19.8	13	50	400	Yes
C25-C25ST	tap connection; joint connection	25	16 - 25	17	21.4	13	50	300	Yes
C35-C16ST	tap connection; joint connection; joining two running conductors	35 - 40; 25	1.5 - 16; 25	21	24.6	15.4	25	200	Yes
C35-C35ST	tap connection; joint connection; joining two running conductors	50; 35 - 40; 35	10 - 25; 25 - 40; 35	21	26.6	15.6	25	200	Yes
C70-C25N-ST	tap connection; joint connection	63 - 70	1.5 - 25	21	26.4	17.5	50	200	Yes
C50-C25ST	tap connection; joint connection	50	4 - 25	25	32.9	21	25	75	Yes
C50-C50ST	tap connection; joint connection	50	35 - 50	26	33	21	25	75	Yes
C70-C35ST	tap connection; joint connection	50 - 70	4 - 40	28	33	21	25	75	Yes
C70-C70ST	tap connection; joint connection; joining two running conductors	50 - 70; 50	35 - 70; 50	28	34	21	25	75	Yes
C95-C35ST	tap connection; joint connection	95 - 100	4 - 40	29	40.6	26	25	50	Yes
C95-C70ST	tap connection; joint connection; joining two running conductors	95 - 100; 63 - 70	40 - 70; 63 - 70	29	41	26	25	50	Yes
C95-C95ST	tap connection; joint connection	95 - 100	63 - 100	29	41	26	25	50	Yes
C120-C120ST	tap connection; joint connection	110 - 125	25 - 125	30	45	28	15	30	Yes
C150-C120ST	tap connection; joint connection; joining two running conductors	125; 150 - 160; 95 - 120	125; 25 - 125; 95 - 120	31	45	28	15	30	Yes
C150-C150ST	tap connection; joint connection; joining two running conductors	125; 150; 125	125; 63 - 150; 125	30	45	28	15	30	Yes
C185-C95ST	tap connection; joint connection; joining two running conductors	185; 120 - 125	16 - 100; 120 - 125	31	45	28	15	30	Yes
C185-C185ST	tap connection; joint connection	120 - 185	120 - 185	22.6	68	34	15	30	Yes

tipo	Type of branch circuit	Cross section range of the through cable [mm²]	Cross section range of the branch cable [mm²]	C [mm]	L [mm]	B [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant
C240-C120ST	tap connection; joint connection	150 - 240	95 - 120	22.6	68	34	15	30	Yes