


TERMO-ROLL H2 LIS

HEAT SHRINK THERMO-ROLL H2 CABLE MARKER, SHRINK RATIO 2:1, HIGH GRADE, ON LADDER, PRINTABLE ON ONE SIDE ONLY



Features

TECHNICAL INFORMATION

Minimum operating temperature	-55°C
Maximum operating temperature	105°C
Minimum shrinkage temperature	90°C
Shrinkage ratio	2:1

CLASSIFICATION AND DATA ORDERING

Customs code	39173200
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Material	Irradiated polyolefin
Halogen free	Yes

CERTIFICATIONS

EN 50343 Annex H certification	Yes
LUL C3349 certification	Yes
MIL-STD-202H Method 215 certification	Yes
NFPA 130 certification	Yes
SAE AS-5942 certification	Yes
Cembre internal test	Yes
CEI EN 61010-1 ed.2	Yes
CEI 16-7	Yes



TERMO-ROLL H2 LIS

tipo	Colour	Range of cable cross section [mm²]	Ø [mm]	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN 45545-2 certification (r22)	EN 45545-2 certification (r23)
H2-24-25-YE1	yellow	0.25 - 0.5	1.6 - 2	2.4	25	2000	2000	Yes	HL3	HL3
H2-32-12.5-YE1	yellow	0.5 - 1	1.8 - 2.8	3.2	12.5	4000	4000	Yes	HL3	HL3
H2-32-25-YE1	yellow	0.5 - 1	1.8 - 2.8	3.2	25	2000	2000	Yes	HL3	HL3
H2-32-50-YE1	yellow	0.5 - 1	1.8 - 2.8	3.2	50	1000	1000	Yes	HL3	HL3
H2-48-12.5-YE1	yellow	1 - 2.5	2.8 - 4.2	4.8	12.5	4000	4000	Yes	HL3	HL3
H2-48-25-YE1	yellow	1 - 2.5	2.8 - 4.2	4.8	25	2000	2000	Yes	HL3	HL3
H2-48-50-YE1	yellow	1 - 2.5	2.8 - 4.2	4.8	50	1000	1000	Yes	HL3	HL3
H2-64-12.5-YE1	yellow	4 - 6	4.2 - 5.8	6.4	12.5	4000	4000	Yes	HL3	HL3
H2-64-19-YE1	yellow	4 - 6	4.2 - 5.8	6.4	19	2000	2000	Yes	HL3	HL3
H2-64-25-YE1	yellow	4 - 6	4.2 - 5.8	6.4	25	2000	2000	Yes	HL3	HL3
H2-64-38-YE1	yellow	4 - 6	4.2 - 5.8	6.4	38	1000	1000	Yes	HL3	HL3
H2-64-50-YE1	yellow	4 - 6	4.2 - 5.8	6.4	50	1000	1000	Yes	HL3	HL3
H2-95-12.5-YE1	yellow	10 - 16	5.8 - 8	9.5	12.5	2000	2000	Yes	HL3	HL3
H2-95-25-YE1	yellow	10 - 16	5.8 - 8	9.5	25	1000	1000	Yes	HL3	HL3
H2-95-50-YE1	yellow	10 - 16	5.8 - 8	9.5	50	500	500	Yes	HL3	HL3
H2-127-50-YE1	yellow	25 - 35	8 - 11	12.7	50	500	500	Yes	HL3	HL3
H2-190-50-YE1	yellow	35 - 50	11 - 17	19.1	50	500	500	Yes	HL3	HL3
H2-254-50-YE1	yellow	50 - 120	17 - 23	25.4	50	300	300	Yes	HL3	HL3
H2-24-6.25-WH1	white	0.25 - 0.5	0.25 - 0.5	2.4	6.25	8000	8000	Yes		
H2-24-12.5-WH1	white	0.25 - 0.5	1.6 - 2	2.4	12.5	4000	4000	Yes	HL3	HL3
H2-24-25-WH1	white	0.25 - 0.5	1.6 - 2	2.4	25	2000	2000	Yes	HL3	HL3
H2-24-50-WH1	white	0.25 - 0.5	1.6 - 2	2.4	50	1000	1000	Yes	HL3	HL3

tipo	Colour	Range of cable cross section [mm²]	Ø [mm]	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN 45545-2 certification (r22)	EN 45545-2 certification (r23)
H2-32-12.5-WH1	white	0.5 - 1	1.8 - 2.8	3.2	12.5	4000	4000	Yes	HL3	HL3
H2-32-25-WH1	white	0.5 - 1	1.8 - 2.8	3.2	25	2000	2000	Yes	HL3	HL3
H2-32-50-WH1	white	0.5 - 1	1.8 - 2.8	3.2	50	1000	1000	Yes	HL3	HL3
H2-48-12.5-WH1	white	1 - 2.5	2.8 - 4.2	4.8	12.5	4000	4000	Yes	HL3	HL3
H2-48-25-WH1	white	1 - 2.5	2.8 - 4.2	4.8	25	2000	2000	Yes	HL3	HL3
H2-48-50-WH1	white	1 - 2.5	2.8 - 4.2	4.8	50	1000	1000	Yes	HL3	HL3
H2-64-12.5-WH1	white	4 - 6	4.2 - 5.8	6.4	12.5	4000	4000	Yes	HL3	HL3
H2-64-25-WH1	white	4 - 6	4.2 - 5.8	6.4	25	2000	2000	Yes	HL3	HL3
H2-64-38-WH1	white	4 - 6	4.2 - 5.8	6.4	38	1000	1000			
H2-64-50-WH1	white	4 - 6	4.2 - 5.8	6.4	50	1000	1000	Yes	HL3	HL3
H2-95-12.5-WH1	white	10 - 16	5.8 - 8	9.5	12.5	2000	2000	Yes	HL3	HL3
H2-95-25-WH1	white	10 - 16	5.8 - 8	9.5	25	1000	1000	Yes	HL3	HL3
H2-95-50-WH1	white	10 - 16	5.8 - 8	9.5	50	500	500	Yes	HL3	HL3
H2-127-50-WH1	white	25 - 35	8 - 11	12.7	50	500	500	Yes	HL3	HL3
H2-190-50-WH1	white	35 - 50	11 - 17	19.1	50	500	500	Yes	HL3	HL3
H2-254-50-WH1	white	50 - 120	17 - 23	25.4	50	300	300	Yes	HL3	HL3
H2-381-50-WH1	white	120 - 240	23 - 36	38.1	50	100	100	Yes	HL3	HL3
H2-508-50-WH1	white	240 - 400	23 - 48	50.8	50	100	100	Yes	HL3	HL3