

P-PPL

HOOK TERMINAL, PRE-INSULATED WITH POLYCARBONATE, FOR COPPER CONDUCTORS, HALOGEN FREE



CERTIFICATIONS & APPROVALS



Features

TECHNICAL INFORMATION

Minimum operating temperature	-20°C
Maximum operating temperature	115°C
Threshold of operating temperature for short periods	130°C
Type of insulation	partial
Easy insertion input	Yes
Surface treatment	tin plating
Crimping geometry	radial

WEIGHT AND DIMENSIONS

Tip type	Hooked blade
Tip length	17.5mm

CLASSIFICATION AND DATA ORDERING

Customs code	85369010
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS


Conductor body material	Rame elettrolitico con purezza superiore al 99,95%
Insulated cover material	Polycarbonate
Annealing	Yes
Halogen free	Yes

LOGISTIC

Unit in minimal packaging	100PCE
---------------------------	--------

CERTIFICATIONS

ROHS compliant	Yes
EN 45545-2 certification	HL2
EN 45545-2 certification	HL3
Self-extinguishing fire class according to UL 94	V0
UL standard	486A-486B



RP-PPL Insulated cover colour **red** Range of cable cross section [mm²] **0.25**

tipo	B [mm]	X [mm]	L [mm]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
RP-PPL30	3	1.737	28.4	4.2	10.1	4	5.5	1.8	5	3000
RP-PPL46	4.6	1.737	28.4	4.2	10.1	4	5.5	1.8	5	3000

BP-PPL Insulated cover colour **blue** Range of cable cross section [mm²] **1.5**

tipo	B [mm]	X [mm]	L [mm]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
BP-PPL30	3	1.737	28.4	4.2	10.1	4.9	6.4	2.4	5	2500
BP-PPL46	4.6	1.737	28.8	4.2	10.1	4.9	6.4	2.4	5	2500

GP-PPL Insulated cover colour **yellow** Range of cable cross section [mm²] **4**

tipo	B [mm]	X [mm]	L [mm]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Unit in standard packaging [pce]
GP-PPL46	4.6	1.966	32.6	8	14.1	6.6	8.1	3.6	7	1000



Via Serenissima, 9 - 25135
Brescia - ITALY