

FD

FLAT SEALING RINGS, NEOPRENE 80 sh A



Features

TECHNICAL INFORMATION

Minimum operating temperature	-25°C
Maximum operating temperature	100°C
Colour	black

CLASSIFICATION AND DATA ORDERING


Customs code	40169300
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Material	Neoprene
----------	----------

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	HB
--	----



FD

tipo	H [mm]	ØI [mm]	ØE [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant
FD7	1.2	11.3	17	50	3000	Yes
FD9	1.2	13.9	20	50	2000	Yes
FD11	1.2	17.1	23	50	2000	Yes
FD13.5	1.2	19	25	50	2500	Yes
FD16	1.2	21	27	50	1500	Yes
FD21	1.5	27	34.5	50	1000	Yes
FD29	1.5	35.2	45	25	500	Yes
FD36	1.2	45.6	53.5	25	250	Yes
FD42	1.1	52	62	10	10	Yes
FD48	1.1	58	68	10	500	Yes
FDM16	1.2	15.5	20	50	50	Yes
FDM12	1.2	10	16	50	2500	Yes
FDM20	1.2	18	24	50	2000	Yes
FDM25	1.2	23	31	50	1000	Yes
FDM32	1.3	30	36	20	600	Yes
FDM40	1.2	38	46	20	500	Yes
FDM50	1.1	47.5	55	10	800	Yes
FDM63	1.1	59	68	5	400	Yes