


## DB/4

DBLOCK SERIES FOUR-POLE DISTRIBUTION BLOCK, DIRECT CLAMPING



### CERTIFICATIONS & APPROVALS



## Features

### TECHNICAL INFORMATION

Cover colour	transparent
Geometry of the clamping element	slotted screw
Easy insertion input	Yes
Captive screw	Yes
Clamping type	direct
Attachment for DIN rail	Yes

### WEIGHT AND DIMENSIONS

Number of poles	4
Height	90mm
Width	50mm

### CLASSIFICATION AND DATA ORDERING

Customs code	85369010
--------------	----------

### MATERIAL COMPOSITION AND TREATMENTS

Conductor body material	brass
Surface treatment of the conductor body	electrolytic tin plating
Cover material	Polycarbonate
Halogen free	Yes
Clamping element material	Zinc plated steel
Insulated body material	Polyamide PA6.6
Surface treatment of the clamping element	Zinc plating
Insulated body colour	grey

### LOGISTIC

Unit in minimal packaging	1PCE
Unit in standard packaging	1PCE

### CERTIFICATIONS

Self-extinguishing fire class according to UL 94	V0
--	----



**DB/4**

tipo	Number and diameter of input holes	Number and diameter of output holes	Torque of the clamping element (6+16 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (1.5+4 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (1.5+6 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (6+16 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (1.5+16 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (2.5+6 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (4+10 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (10+50 mm <sup>2</sup> f/f) [Nm]	Torque of the clamping element (2.5+25 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (10+35 mm <sup>2</sup> f/f) [Nm]	Torque of the clamping element (0.75+4 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (10+35 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (10+25 mm <sup>2</sup> f/f) [Nm]	Torque of the clamping element (10+25 mm <sup>2</sup> f) [Nm]	Torque of the clamping element (10+25 mm <sup>2</sup> f) [Nm]	Operating current [A]	Rated short-time withstand current ICW [kA]
DB40-11/4	2x6 mm	11x4.3 mm		1.5		3			3				1.5					40	4.5
DB100-6/4	1x8.5 mm	3x4.5 mm; 3x5.5 mm		1.5	3			3					1.5		3			100	4.5
DB100-13/4	2x8.5 mm	6x4.5 mm; 7x5.5 mm		1.5	3			3					1.5		3			100	4.5
DB125-6/4	1x9.5 mm	5x5.5 mm; 1x7.5 mm	3		3			3					7			3		125	4.5
DB125-10/4	1x9.5 mm	7x5.5 mm; 3x7.5 mm	3		3			3					7			3		125	4.5
DB125-14/4	1x9.5 mm	11x5.5 mm; 1x7.5 mm; 1x8.5 mm	3		3			3					7		3	3		125	4.5
DB160-11/4	1x12 mm	3x8.5 mm; 7x7.2 mm; 1x5.5 mm			3		3	3		10	3			3			3	160	8.2
DB125-10/4C	2x8.5 mm	7x5.3 mm; 2x7.5 mm	3		3			3						3		3		125	4.5
DB125-14/4C	2x8.5 mm	11x5.3 mm; 2x7.5 mm	3		3			3						3		3		125	4.5