


# 1052

PLUG, IN POLYAMIDE PA6, PG PITCH, IP54



**CERTIFICATIONS & APPROVALS**

 UL (cULus)

## Features

**TECHNICAL INFORMATION**

Range of operating temperature (dynamic)	-20°C
Range of operating temperature (static)	-40°C
Threshold of operating temperature for short periods	110°C

**MATERIAL COMPOSITION AND TREATMENTS**


**Material** Polyamide PA6

**CLASSIFICATION AND DATA ORDERING**

**Customs code** 39269097

**CERTIFICATIONS**

<b>ROHS compliant</b>	Yes
<b>Self-extinguishing fire class according to UL 94</b>	HB
<b>Ingress Protection</b>	IP54



## 1052

tipo	P	Colour	Tightening torque (plug) [nm]	Tightening torque (locknut) [nm]	C [mm]	ØF [mm]	Width [mm]	H [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	UL standard	EN ISO 4892-2
1052007	Pg7	grey	1	1.5	6	12.7	15	8	100	100	514A	Yes
1052007N	Pg7	black	1	1.5	6	12.7	15	8	100	100	514A	Yes
1052009	Pg9	grey	1	1.5	6	15.5	19	9	100	100		
1052009N	Pg9	black	1	1.5	6	15.5	19	9	100	100		
1052011	Pg11	grey	1.5	3	7	18.8	22		100	100		
1052011N	Pg11	black	1.5	3	7	18.8	22		100	100		
1052013	Pg13.5	grey	1.5	3	7	20.5	25		100	100		
1052013N	Pg13.5	black	1.5	3	7	20.5	25		100	100		
1052016	Pg16	grey	1.5	3	7	22.6	27		100	100		
1052016N	Pg16	black	1.5	3	7	22.6	27		100	100		
1052021	Pg21	grey	1.5	3	9	28.5	33		50	50	514A	Yes
1052021N	Pg21	black	1.5	3	9	28.5	33		50	50	514A	Yes
1052029	Pg29	grey	3	6	9	37.2	44		25	50		
1052029N	Pg29	black	3	6	9	37.2	44		25	50		
1052036	Pg32	grey	6	10	10	47.2	55	15	20	20	514A	Yes
1052036N	Pg32	black	6	10	10	47.2	55	15	20	20	514A	Yes
1052042	Pg42	grey	6	10	10	54.2	62	16	10	10	514A	Yes
1052042N	Pg42	black	6	10	10	54.2	62	16	10	10	514A	Yes
1052048	Pg48	grey	6	10	12	60	69	18	10	10	514A	Yes
1052048N	Pg48	black	6	10	12	60	69	18	10	10	514A	Yes