

CPKD



Features

TECHNICAL INFORMATION

Minimum operating temperature	-20°C
Maximum operating temperature	115°C
Threshold of operating temperature for short periods	130°C
Easy insertion input	Yes
Surface treatment	tin plating
Crimping geometry	trapezium

WEIGHT AND DIMENSIONS

Cover length	6mm
Cable stripping length	8mm
Body length	8mm
Total length	14mm

CERTIFICATIONS


Self-extinguishing fire class according to UL 94	V2
--	----

MATERIAL COMPOSITION AND TREATMENTS

Conductor body material	Rame elettrolitico con purezza superiore al 99,95%
Insulated cover material	Polypropylene
Halogen free	Yes

CLASSIFICATION AND DATA ORDERING

Customs code	85369010
--------------	----------



CPKD

tipo	Insulated cover colour	Range of cable cross section [mm ²]	Ø2 [mm]	Ø1 [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant
CPKD508	white	0.3 - 0.5	2.6	1.3	5000	5000	Yes
CPKD7508	grey	0.75	2.8	1.5	5000	5000	Yes
CPKD108	red	1	3	1.7	5000	5000	Yes
CPKD1508	black	1.5	3.5	2	5000	5000	Yes
CPKD2508	blue	2.5	4.2	2.5	3000	3000	Yes



