


CUSTOMER DRAWING


① MMCII04F-W



ISO VIEW








- NOTE -

1. BEFORE USING, CHECK THE HARMFUL CRACK, BURR, ETC.
2. GENERAL TOLERANCES - SEE BLOW.
3. MARKING & CAV No. BY AS GENERAL RULE OF KUM.
4. ASSY PART


1) TERMINAL △1


APPLICATION WIRE(SQ)	KUM PART NAME	KUM P/NO.	APTIV P/NO.
AVSS 0.3~0.5sq	TML MMCII-F-S	TK196-00100	35298383
	TML MMCII-F-S-Au	TK196-00110	35298384
CHFUS 0.22sq	TML MMCII-F-SS	TK196-00400	35298385
	TML MMCII-F-SS-Au	TK196-00410	35298386


② MMCII04FA-B




ISO VIEW









③ S/H MMCII04F-OR



ISO VIEW







NO.	KUM PART NAME	KUM P/No.	APTIV P/No.	COLOR	MATERIAL
③	S/H MMCII04F-OR	HK915-04100	35298168	ORANGE	PBT
②	MMCII04FA-B	HK876-04020	35297674	BLACK	PBT
①	MMCII04F-W	HK875-04010	35297673	WHITE	PBT

THIRD ANGLE PROJECTION	A	-	JJS	JJS	KDK	CJW
	TOLERANCE	SCALE	DESIGN	DRAWN	CHECKED	APPROVED

GENERAL TOLERANCE									
	10MAX	30MAX	50MAX	70MAX	100MAX	120MAX	250MAX	250VR	ANGLE
A	±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'

승인	DATE	NOTE No.	SYM	ALTERATION	담당
	21.06.09	-	△1	ADDED APTIV P/No.	YYJ
CJW	17.05.26	E017-0220	△-	신 규	JJS

DRAWING NAME	MMCII04F-W
DRAWING No.	HK875-04010-C01

APTIV